

60

HRC series

60X60X25mm

● SPECIFICATION

- Motor: DC unidirectional brushless motor
- Material
 - Outer frame: PBT engineering plastic (94V-0)
 - Fan blade: PBT engineering plastic (94V-0)
 - Life: L10 at 40°C temperature (varies with operating environment)
 - Double ball: 50,000 hours
- Weight: 55 grams



model	bearing	Voltage	operating voltage	current	Rotating speed	Maximum air volume	maximum wind pressure	noise	P-Q curve		
	B / S / F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	No.
HRC06025_12H	B / F	12	7.0~13.2	0.60	5000	0.81	28.54	8.01	0.32	37	⑤

● Environmental Specifications

- 10°C~70°C (Operating Conditions: Jun Gongzhu)
- 10°C~50°C (Operating condition: FMB bearing/oil bearing)
- 40°C~80°C (Storage environment)
- To have condensation

● Electrical Specifications


Absolute strength: 500V/min, the maximum leakage current is 500mA
 Withstand voltage resistance: minimum 10 megohm DC 500V

Speed signal		speed control		
FG**	RD	PWM	Temperature	Voltage
△	△	△	X	X

Protection			IP
automatic reset	polarity	lock	
△	△	○	△

**FG means speed outp
 ○: yes △ : optional X:None.

● characteristic curve



● Drawing

