

# DC Axial

**SIZE/尺寸：80X80X25mm**

## General Specifications (一般規格)

Motor : DC Brushless motor

馬達：直流單向無刷馬達

Frame : plastic(94V-0)

材料：框：塑料 (94V-0)

Impeller : plastic(94V-0)

材料：葉：塑料 (94V-0)

Bearing : Ball bearing; Sleeve; FMB

軸承：滾珠軸承; 含油軸承; FMB

Weight : 80g

重量：80克



## Major Characteristic Parameters 主要參數

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max Air Flow	Max Static Pressure	Sound		
機型	軸承	電壓	操作電壓	電流	轉速	最大風量	最大風壓	噪音		
Part NO.	B / F / S	V	V	A	RPM	m3/min	CFM	mm-H2O	In-H2O	dBA
K-DC08025-A5-27	B/F/S	5	4.5~5.5	0.25	2700	0.90	31.80	2.90	0.12	28
K-DC08025-A12-27	B/F/S	12	7.0~13.2	0.14	2700	0.90	31.80	2.90	0.12	29
K-DC08025-A12-30	B/F/S	12	7.0~13.2	0.19	3000	1.00	35.40	3.60	0.15	33
K-DC08025-A12-36	B/F/S	12	7.0~13.2	0.32	3600	1.20	42.40	5.00	0.20	38
K-DC08025-A12-43	B/F/S	12	7.0~13.2	0.40	4300	1.43	50.50	6.80	0.28	43
K-DC08025-A12-50	B/F	12	7.0~13.2	0.50	5000	1.70	60.00	9.60	0.39	48
K-DC08025-A24-27	B/F/S	24	14.0~26.4	0.08	2700	0.90	31.80	2.90	0.12	29
K-DC08025-A24-30	B/F/S	24	14.0~26.4	0.11	3000	1.00	35.40	3.60	0.15	33
K-DC08025-A24-36	B/F/S	24	14.0~26.4	0.18	3600	1.20	42.40	5.00	0.20	38
K-DC08025-A24-43	B/F/S	24	14.0~26.4	0.26	4300	1.43	50.50	6.80	0.28	43
K-DC08025-A24-50	B	24	14.0~26.4	0.28	5000	1.70	60.00	9.60	0.39	48
K-DC08025-A48-30	B/F/S	48	28.0~56.0	0.06	3000	1.00	35.40	3.60	0.15	33
K-DC08025-A48-36	B/F/S	48	28.0~56.0	0.09	3600	1.20	42.40	5.00	0.20	38
K-DC08025-A48-43	B/F/S	48	28.0~56.0	0.16	4300	1.43	50.50	6.80	0.28	43
K-DC08025-A48-50	B	48	28.0~56.0	0.21	5000	1.70	60.00	9.60	0.39	48

## Drawing & panel out-cuts 圖面及出入風口

## Characteristic Curves 特性曲線

